

# The Light Source

## 24" Mega-Truss Pick



1" x 6" x 25-3/8" 6061T-6 Aluminum CNC machined with pockets to support one piece of 24" truss. Truss is secured by two aluminum pivoting links, half inch swivel bolts, and our solid wing nuts. Has two rigging holes for shackles, motor, or chain hook. The Mega-Truss Pick will suspend one ton of truss load , and an additional pass through load of one ton.

The Mega-Truss Pick has one top and one bottom rigging hole for attaching the truss to a shackle, motor, or chain hook. The Mega-Truss Pick will suspend up to one ton of truss load, plus an additional one ton load suspended under the truss. . Fits 5/8" Shackle and larger.

Please note that these do not fit a Global Truss or Applied Truss. See Global Truss Picks for correct part # to order. For Applied Truss you will need to call us with specifications.

<b>Working Load Limit</b>	1 Ton
<b>Hardware</b>	1/2"-13 steel swivel eyebolts with our solid aluminum wing nuts
<b>Dimensions</b>	1" x 6" x 25-3/8"; Actual single hole is 1.5" wideActual single multi-hole is 5/8" wide
<b>Weight</b>	10.4 pounds
<b>Case Quantities</b>	Each
<b>Order Codes</b>	<b>MT P24</b> 24" Mega-Truss Pick, Silver <b>MT P24MH</b> 24" Mega-Truss Pick, Silver