The Light Source

Mega-Drop Down



The Mega-Drop Down is a quick and inexpensive way to place a light fixture below the pipe or grid. It now has new wrench flats for easy adjustments.

The Mega-Drop Down is made from solid 3/4" diameter 6061 T-6 aircraft grade aluminum and is made in 6", 9", 12", 18" 24", and 36" lengths. The Mega-Drop Down has a 1/2-13 tpi x 2" steel stud to fasten into a Mega-Clamp, or similar damp that has 1/2"-13 female threads. The lower end of the Mega-Drop Down has 1/2-13 female threads to bolt the light fixture's yoke to the drop down with a 1/2-13 × 1" grade 5 zinc plated bolt and Belleville washer. When assembling the Drop down to the Mega-Clamp, use Loctite Red or other permanent thread-locking compound to make the connection secure.

METRIC

Available in M-10 and M-12.

Working Load 600 Pounds

Limit

Hardware 1/2-13 tpi x 2" Steel stud to fasten into a Mega-Clamp.

1/2"-13 × 1" grade 5 hex head zinc plated cap screw with

our Belleville washer

Dimensions 3/4" Diameter x 6"+

Weight MDDB6 – 0.39lbs (MDDB9 – .51 lbs.) MDDB12 – 0.66lbs

 $\mathsf{MDDB18} - \mathsf{0.92lbs} \,\, \mathsf{MDDB24} - \mathsf{0.97lbs} \,\, \mathsf{MDDB36} - \mathsf{1.7lbs}$

Case Quantities ead