The Light Source

Mega-Quick Pipe Splice



Quickly joins two pipes in line together without drilling or threading for permanent or temporary installations. The Mega-Quick Pipe Splice is the same outside diameter as the pipe for a nice flush look and feel. Install by loosening the set screw one half turn with a quarter inch hex key to open the splice. Align the set screw so that it will be on the side of the pipe joint. (This will give the maximum strength to the joint.) Pinch the bars together at one end, and insert the splice into the first pipe. Then pinch the other ends of splice together and insert the splice into the second pipe. Slide the pipes tightly toward the splice and tighten the set screw securely with the one quarter inch hex key. Bolts should be tightened to about 30 foot pounds.

For I I/2" pipe in black or mill, schedule 40 or schedule 80. Also available for I I/4" pipe in schedule 40. Weight one pound.

Working Load

600 Pounds Horizontal, Not rated for vertical use

Limit

Hardware 1/2-13 socket set screw

Dimensions 8.25" in total length Piece in middle is I" wide

Weight 15 oz.

Case Quantities 12

Order Codes MQSB-I-I/4 Mega-Quick Pipe Splice for I-I/4 Sch. 40

Pipe, Black Anodized

MQSM-I-I/4 Mega-Quick Pipe Splice for I-I/4" Sch. 40

Pipe, Silver

MQS B80 Mega-Quick Pipe Splice for 1-1/2" Sch. 80 Pipe,

Black Anodized

MQS M80 Mega-Quick Pipe Splice for I-I/2" Sch. 80 Pipe,

Silver

MQSM Mega-Quick Pipe Splice for I-I/2" Sch. 40 Pipe,

Silver

MQSB Mega-Quick Pipe Splice for I-I/2" Sch. 40 Pipe,

Black Anodized

MQS B80- I- I/4 Mega-Quick Pipe Splice for I-I/4" Sch.

80 Pipe, Black Anodized

 $\textbf{MQS\,M80-I-I/4} \ \text{Mega-Q\,uidk Pipe Splice for I-I/4" Sch.}$

80, Black Anodized

MQSW Mega-Quick Pipe Splice for 1-1/2" Sch. 40 Pipe,

White Powder Coat

MQSW80 Mega-Quick Pipe Splice for I-I/2" Sch. 80,

White Powder Coat