The Light Source

Mega-Swivel Coupler



The Swivel Coupler will fasten from I-I/4" pipe (1.660" O D) to 2.050" O D truss tube. The Swivel-Coupler has wide wing nuts for fastening the damp to the pipe or tube.

The Swivel Coupler can be locked into a 90 degree fixed coupler by adding an optional $7/32^{\prime\prime} \times 2^{\prime\prime}$ spirol pin.

The Swivel Coupler is available with a Steel Wingnut(SW), and Stainless Steel Hardware (SS) options.

Minimum Size 1.25" pipe, 1.66" OD pipe

Maximum Size 1.5" pipe, 1.90" OD pipe, 2" OD truss tube

Working Load 1,100 Pounds 500kg

Limit

Weight 22 Pounds

Case Quantities

Order Codes MLS M Mega-Swivel Coupler, Silver

MLSB Mega-Swivel Coupler, Black Anodized

MLSM-SW Mega-Coupler, Swivel with Steel Wingnut,

Silver

MLSMSS Swivel Coupler with Stainless Steel

Hardware, Silver

MLSB-SW Mega-Coupler, Swivel with Steel Wingnut,

Black An odized

MLSBSS Swivel Coupler with Stainless Steel

Hardware, Black Anodized

MLSW Mega-Coupler, Swivel, White Powder Coat

 $\textbf{MLSB-NN} \ \mathsf{Mega-Coupler}, \ \mathsf{Swivel}, \ \mathsf{Nylock} \ \mathsf{Nut}, \ \mathsf{Black}$

Anodized

MLS BSS-NN Swivel Coupler with Stainless Steel Hardware & Nylodk Nut on the Bolt Assembly, Bladk

MLS MSS-NN Swivel Coupler with Stainless Steel Hardware & Nylock Nut on the Bolt Assembly, Silver

MLSBSS-SW Swivel Coupler with Stainless Steel

Hardware, and Stainless Steel Wingnut, Black Anodized MLSMSS-SW Swivel Coupler with Stainless Steel

Hardware, and Stainless Steel Wingnut, Silver